


# SonicSert



Type: Sonic



Type: SonicH (headed)



Sonic/SonicH (headed)

## Material Code

B = brass

## General information

- Permits thin boss walls.
- Opposed helical knurl bans to provide high torque and pull out resistance.

## How to order

Type + Thread + Alt. Length (if applicable) + Material Code

Example: Sonic-M4-B or Sonic-M6-9.5-B or SonicH-M5-B (headed)

Thread	L mm	B mm	C mm	K mm	N mm	Rec. Hole Size - 0.00 / + 0.10 mm	Min. Wall Thickness mm	Please note!
M2	4.0	0.53	4.8	3.6	3.1	3.2	1.3	
M2.5	5.7	0.61	5.5	4.6	3.9	4.0	1.6	
M3	5.7	0.61	5.5	4.6	3.9	4.0	1.6	
M3.5	7.1	0.76	6.4	5.4	4.7	4.8	1.8	
M4	8.1	0.91	7.1	6.3	5.5	5.6	2.1	Alt. L= 4.8 & 5.8
M5	9.5	1.09	7.9	7.1	6.3	6.3	2.6	Alt. L= 5.8
M6	12.7	1.35	9.5	8.7	7.9	8.0	3.3	Alt. L=9.5
M8	12.7	1.35	11.1	10.2	9.5	9.6	4.5	
M10	12.7	1.60	14.0	12.6	11.8	11.9	6.0	