


# ThreadSert



Type: Thread



Type: ThreadH (headed)



Thread/ThreadH (headed)

## Material Code

B = brass.

If steel (S) or stainless steel (SS) is required, please contact our sales dept.

## General information

- High pull-out resistance.
- Ideal where jack-out loading is unavoidable.
- Can carry high loads in weak plastics.

## How to order

Type + Thread + Alt. Length (if applicable) + Material Code

Example: Thread-M4-B or ThreadH-M4-B

Thread	L mm	B mm	C mm	K mm	Rec. Hole Size -0.00 / +0.10 Thermoplastic mm	Rec. Hole Size -0.00 / +0.10 Thermosets mm	Min. Wall Thickness mm	Bemærk!
M2.5	6.0	0.58	6.0	4.5	4.0 - 4.1	4.1 - 4.3	Pre-production tests	
M3	6.0	0.58	6.5	5.0	4.5 - 4.6	4.6 - 4.8	Pre-production tests	
M3.5	8.0	0.73	7.5	6.0	5.2 - 5.4	5.5 - 5.7	Pre-production tests	
M4	8.0	0.89	8.0	6.5	5.8 - 5.9	6.0 - 6.2	Pre-production tests	
M5	10.0	1.06	9.5	8.0	7.1 - 7.2	7.3 - 7.6	Pre-production tests	
M6	14.0	1.32	12.0	10.0	8.6 - 8.8	9.0 - 9.4	Pre-production tests	
M8	15.0	1.32	14.0	12.0	10.6 - 10.8	11.0 - 11.4	Pre-production tests	
M10	18.0	1.57	16.0	14.0	12.6 - 12.8	13.0 - 13.4	Pre-production tests	